




Technical datasheet No.: **1040.6**
Product: POLYMAR* Side Curtain
Article No.: 8556 5240

Type of coating and finish			
Type of coating	PVC		
Finish	both sides laacquered, High gloss		
Burning behaviour	ISO 3785 <100 mm/min.		
Total weight	800 g/m ²	EN ISO 2286-2	
Tensile strength warp/weft	4300 / 4000 N/50 mm	EN ISO 1421/V1	
Tear strength warp/weft	600 / 600 N	DIN 53363	
Adhesion	20 N/cm	FA 09.03 (inter)	
Cold resistance	-40 °C	EN 1576-1	
High Temperature	+70 °C	FA 07.04 (inter)	
Light fastness	>8 Note, Value	EN ISO 105 B02	
Crack resistance	no cracks 100000 x	DIN 53359 A / DIN EN ISO 7854 B	
Base fabric			
Material	PE5	DIN EN ISO 2076	
Yarn count	1100 dtex	DIN EN ISO 2060	
Weave	P 2/2		
Remarks	complies with EN 12641-2, materials		

These indicated technical data are  in average results. Due to production procedures deviations up to ±5% can occur. All technical data are in accordance with the present state of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.



QIA-071/3-08/00
EA/007-06/98

VULB:
Date 29.10.2017

Joan.Fabillano

Reply X

you can only see the Low & Bonar logo at the bottom

11/21/2017 12:32 PM

Post